

Technical Specification Crafft

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >30 watts Medium size rooms: >70 watts Large size rooms: -- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.7 - 9.3ohms
Impedance, (200 - 20 kHz):	3.7 - 5.8 ohms
Impedance, Phase Shift (20 - 200 Hz):	-31.0° - +5.8°
Impedance, Phase Shift (200 - 20 kHz):	-3.6° - +11.0°
Impedance, HF (200 kHz):	6.1 ohms
Frequency Response (+/- 3 dB):	38 Hz - 22 kHz
Resonance Frequency:	42 Hz
Internal Cabinet Volume:	15 litres
Bass Principle:	Bass reflex
Weight:	10.9 kg
Dimensions (W x H x L):	220 x 400 x 280 mm
Crossover:	2 way. Crossover is impedance corrected
Crossover Frequencies:	3200 Hz
Crossover Slope:	Woofer: 12 dB/oct, Tweeter: 12 dB/oct
Connection:	Gold binding posts
Recommended Placing:	Stand
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. Pure aluminium wire voice coil. Woofer: 17 cm with 75 mm pure aluminium wire voice coil. Adjustable tweeter and midrange level. High quality polypropylene capacitors. Only high quality air coils are used.

DYNAUDIO Vertriebs GmbH

Ohepark 2

D-21224 Rosengarten-Nenndorf

Telefon +49 4108 - 4180 - 0

Telefax +49 4108 - 4180 - 10

e-Mail: sales@dynaudio.de