

OCEAN WAY AUDIO

Pro3 REFERENCE MONITOR



The **Pro3** is our newest addition to the renowned Ocean Way Audio high resolution monitor line. Despite its small size, the Pro3 delivers the same level of extraordinary performance you have come to expect from all of our monitors. Total accuracy and resolution with no hype. When you have created something that sounds great, you will hear every bit of punch and clarity that's in your mix. The frequency response of the Pro3 between channels falls within ± 0.5 db of each other, which is the reason that the imaging on our speakers is dead on. Also the Pro3 has exceptional low-end extension for its physical size, with clear and defined bass down to 45Hz and below... remarkable for a small speaker.



Ocean Way Audio Pro3 Reference Monitor

SPECIFICATIONS & DESIGN DETAILS



Pro3's HF driver is a high definition silk fabric dome design with excellent mechanical linearity. The LF driver uses a geometrically reinforced aluminum cone with a vented cast aluminum chassis yielding optimum strength and "high-power linearity". Combined with the cabinet, the system offers minimal reflection, high resolution and low listening fatigue over the entire audio spectrum.

Our two-way, self-powered design delivers outstanding performance allowing for flexibility of placement in the room with a uniform frequency response of 45Hz to 20kHz, and 110 dB maximum SPL between channels. Its overload protection circuitry ensure that drivers and amplifiers are protected, providing long term system reliability. The speaker allows the professional to hear great detail with a natural, open and accurately image. The Pro3 stands well above competitive monitor speakers in its price range.

Specifications

Powered:	Yes.	Frequency Range:	45Hz-20kHz
Driver Configuration:	2-way	Enclosure Type:	Ported
HF Driver Size/Amp:	1"/90W	Maximum Peak SPL:	110dB
LF Driver Size/Amp:	7"/125W	Dimensions:	9" W x 14"H x 13.5"D
Analog Inputs:	Balanced	Weight:	23 lbs.
AES-3 Digital Inputs:	Yes		